

FLOTATION KING



- High flotation tire design
- Suitable for agricultural implements
- High load capacity at low inflation pressure
- Reduces soil compaction and protects crops
- Angled lugs prevent slippage on uneven terrain
- Sturdy construction and durably compounds ensure long life
- Specially developed stubble guard compound for sugar cane plantations (in selected sizes)

SIZE	PLY RATING	RIM WIDTH (INCH)	TYPE	SECTION WIDTH		OVERALL DIAMETER		STATIC LOADED RADIUS		ROLLING CIRCUM		NSD		LOAD CAPACITY				INFLATION PRESSURE		LOAD INDEX	SPEED	
				MM	INCH	MM	INCH	MM	INCH	MM	INCH	MM	32 ^{nds}	MM	32 ^{nds}	40 KPH	50 KPH	25 MPH	30 MPH		BAR	PSI
400/60-15.5	14	13	TL	400	15.7	875	34.4	381	15.0	2565	101.0	20.0	25	2731	2272	6010	5000	3.8	52	136	A8/40	A8/25
600/50-22.5	16	20.0	TL	600	23.6	1170	46.1	508	20.0	3505	138.0	25.2	32	3600	3256	8050	7165	2.6	38	153	A8/40	A8/25



F-2

- Penetrates deep into soil for maximum steering control and minimal lateral side-slip because of its high center rib
- Best for handling heavy loads on hard-packed surfaces
- Offers excellent load distribution and flotation

SIZE	PLY RATING	RIM WIDTH (INCH)	TYPE	SECTION WIDTH		OVERALL DIAMETER		STATIC LOADED RADIUS		ROLLING CIRCUM		NSD		LOAD CAPACITY		INFLATION PRESSURE		LOAD INDEX	SPEED	
				MM	INCH	MM	INCH	MM	INCH	MM	INCH	MM	32 ^{nds}	KG	LBS	BAR	PSI		KMPH	MPH
7.50-16	8	5.5	TT	205	8.0	808	31.8	381	15.0	2413	95.0	14	18	875	1925	3.8	54	103	A8/40	A8/25
10.00-16	10	7.0	TT/TL	275	10.8	900	35.4	406	16.0	2692	106.0	18	23	1360	2992	2.9	41	119	A8/40	A8/25
11.00-16	12	10	TT/TL	320	12.6	970	38.1	457	18.0	2896	114.0	23	29	1600	3520	2.5	48	124	A8/40	A8/25
7.50-18	8	5.5	TT	204	8.0	867	34.2	406	16.0	2565	101.0	14	18	950	2090	3.8	54	106	A8/40	A8/25
7.50-20	8	6	TT	203	8.0	920	36.2	432	17.0	2718	107.0	16	20	1030	2266	3.5	50	109	A8/40	A8/25



F-3

- Extra wide lugs designed to resist buckling, tearing and cracking
- Excellent tread wear and road ability, the laterally designed lugs result in even wear

SIZE	PLY RATING	RIM WIDTH (INCH)	TYPE	SECTION WIDTH		OVERALL DIAMETER		STATIC LOADED RADIUS		ROLLING CIRCUM		NSD		LOAD CAPACITY		INFLATION PRESSURE		LOAD INDEX	SPEED	
				MM	INCH	MM	INCH	MM	INCH	MM	INCH	MM	32 ^{nds}	KG	LBS	BAR	PSI		KMPH	MPH
11L-15	12	8.0	TL	280	11.0	813	32.0	355	14.0	2362	93.0	8	10	1177	2596	4.1	58	114	A8/40	A8/25
11L-16	12	8.0	TL	280	11.0	820	32.3	381	15.0	2438	96.0	10	14	1250	2750	4.5	64	116	A8/40	A8/25