



GRIPKING R-1

- Deep tread with excellent tread wear and durability
- Designed to deliver power to the ground
- Offers maximum cleaning and hillside slip resistance

SIZE	PLY RATING	RIM WIDTH (INCH)	TYPE	SECTION WIDTH		OVERALL DIAMETER		STATIC LOADED RADIUS		ROLLING CIRCUM		NSD		LOAD CAPACITY		INFLATION PRESSURE		LOAD INDEX	SPEED	
				MM	INCH	MM	INCH	MM	INCH	MM	INCH	MM	INCH	MM	32 ^{NDS}	KG	LBS		BAR	PSI
7-16	6	5.5	TT	183	7.2	740	29.1	333	13.1	2205	86.8	17	21	500	1100	2.5	36	84	A6/30	A6/20
7.50-16	6	5.5	TT	190	7.5	810	31.9	381	15.0	2388	94.0	17	21	1120	2464	3.1	45	112	A8/40	A8/25
9.5-24	8	7.0	TT	241	9.4	1050	41.3	483	19.0	3099	122.0	26	33	1120	2464	2.9	41	112	A8/30	A8/20
11.2-20	8	10.0	TT	284	11.2	998	39.7	483	19.0	2997	118.0	30	38	1090	2398	2.5	36	111	A6/30	A6/20
11.2-24	8	10.0	TT	284	11.2	1105	43.5	508	20.0	3251	128.0	28	35	1250	2750	2.5	36	116	A6/30	A6/20
11.2-24	12	10.0	TT	284	11.2	1105	43.5	508	20.0	3250	128.0	30	38	1360	3000	2.8	40	119	A6/30	A6/20
12.4-24	8	11.0	TT	315	12.4	1170	46.0	533	21.0	3404	134.0	29	36	1450	3190	2.3	33	121	A6/30	A6/20
12.4-24	12	11.0	TT	315	12.4	1170	46.1	533	21.0	3405	134.1	28	36	1800	3960	3.4	50	128	A6/30	A6/20
13.6-24	8	12.0	TT	345	13.5	1210	47.6	559	22.0	3556	140.0	29	36	1500	3300	2.0	28	122	A6/30	A6/20
13.6-24	12	13.0	TT	345	13.6	1210	47.6	559	22.0	3556	140.0	28	36	1900	4180	2.8	41	130	A6/30	A6/20
13.6-28	8	12.0	TT	345	13.6	1320	52.0	584	23.0	3861	152.0	36	45	1650	3630	2.0	28	125	A6/30	A6/20
13.6-38	8	12.0	TT	345	13.6	1565	61.6	737	29.0	4597	181.0	36	45	1950	4290	2.0	28	131	A6/30	A6/20
13.6-28	12	12.0	TT	345	13.6	1320	52.0	584	23.0	3861	152.0	37	47	2120	4664	2.9	42	134	A6/30	A6/20
13.6-38	12	12.0	TT	345	13.6	1565	61.6	737	29.0	4597	181.0	36	46	2430	5360	3.0	44	139	A6/30	A6/20
14.9-24	8	13.0	TT	378	14.9	1265	49.8	584	23.0	3708	146.0	32	40	1800	3960	1.8	26	128	A6/30	A6/20
14.9-24	12	13	TT	378	14.9	1265	49.8	584	23.0	3708	146.0	30	38	2180	4795	2.6	37	135	A6/30	A6/20
14.9-28	8	13.0	TT	378	14.9	1365	53.7	635	25.0	4013	158.0	33	41	1900	4180	1.8	26	130	A6/30	A6/20
14.9-28	12	13.0	TT	378	14.9	1365	53.7	635	25.0	4013	158.0	32	41	2300	5060	2.6	38	137	A6/30	A6/20
16.9-28	8	15.0	TT	429	16.9	1435	56.5	660	26.0	4216	166.0	35	48	2180	4796	1.8	26	135	A6/30	A6/20
16.9-28	12	15.0	TT	429	16.9	1435	56.5	660	26.0	4216	166.0	35	44	2725	5995	2.3	34	143	A6/30	A6/20
16.9-30	12	15.0	TT	429	16.9	1486	58.5	686	27.0	4369	172.0	40	50	2725	5995	2.5	36	143	A6/30	A6/20
18.4-30	8	16.0	TT	467	18.4	1560	61.4	711	28.0	4547	179.0	35	44	2430	5345	1.4	20	139	A6/30	A6/20
18.4-30	12	16.0	TT	467	18.4	1560	61.4	711	28.0	4547	179.0	35	44	3250	7165	2.3	33	149	A6/30	A6/20
18.4-30	14	16.0	TT	467	18.4	1560	61.4	711	28.0	4547	179.0	35	44	3450	7605	2.6	38	151	A6/30	A6/20
18.4-34	8	16.0	TT	467	18.4	1660	65.3	762	30.0	4851	191.0	38	48	2650	5830	1.4	20	142	A6/30	A6/20
18.4-34	12	16.0	TT	467	18.4	1660	65.0	762	30.	4851	191.0	35	44	3000	6600	2.2	32	146	A6/30	A6/20
18.4-34	14	16.0	TT	467	18.4	1660	65.4	762	30.0	4851	191.0	35	44	3750	8270	2.6	38	154	A6/30	A6/20
18.4-38	8	16.0	TT	467	18.4	1770	69.6	813	32.0	5156	203.0	38	48	2725	5995	1.4	20	143	A6/30	A6/20
18.4-38	14	16.0	TT	467	18.4	1770	69.7	813	32.0	5156	203.0	35	44	3650	8030	2.3	33	153	A6/30	A6/20
20.8-38	8	18.0	TT	531	20.9	1834	72.2	864	34.0	5385	212.0	40	50	3150	6930	1.3	19	148	A6/30	A6/20
20.8-38	12	18.0	TT	528	20.8	1840	72.4	864	34.0	5385	212.0	40	51	4000	8800	2.0	29	156	A6/30	A6/20
20.8-38	14	18.0	TT	528	20.8	1840	72.4	864	34.0	5385	212.0		40	4500	9920	2.4	35	160	A6/30	A6/20