

GRIPKING HD R-1



- Superior heavy duty agricultural tire
- Developed for use on high powered tractors and machinery
- Deep solid lugs provide superior traction
- Widest possible inter-lug spacing for efficient self-cleaning
- Wear resistant compound provides long service life

SIZE	PLY RATING	RIM WIDTH (INCH)	TYPE	SECTION WIDTH		OVERALL DIAMETER		STATIC LOADED RADIUS		ROLLING CIRCUM		NSD		LOAD CAPACITY		INFLATION PRESSURE		LOAD INDEX	SPEED	
				MM	INCH	MM	INCH	MM	INCH	MM	INCH	MM	32 ND S	KG	LBS	BAR	PSI		KMPH	MPH
15.5/80-24	12	13.0	TL	394	15.5	1260	49.6	584	23.0	3708	146.0	32	40	2900	6380	3.0	43	145	A6/30	A6/20
23.1-26	12	20.0	TL	587	23.1	1585	62.4	720	28.3	4806	189.2	42	53	3650	8030	1.7	25	153	A6/30	A6/20
23.1-26	16	20	TL	587	23.1	1585	62.4	720	28.3	4806	189.2	42	53	4375	9625	2.3	33	159	A6/30	A6/20



PK-303 I-1

- Low section implement tire for modern farming equipment
- High load capacity with little soil compaction
- Very low rolling resistance
- Designed for high durability

SIZE	PLY RATING	RIM WIDTH (INCH)	TYPE	SECTION WIDTH		OVERALL DIAMETER		STATIC LOADED RADIUS		ROLLING CIRCUM		NSD		LOAD CAPACITY		INFLATION PRESSURE		LOAD INDEX	SPEED	
				MM	INCH	MM	INCH	MM	INCH	MM	INCH	MM	32 ND S	KG	LBS	BAR	PSI		KMPH	MPH
10.0/75-15.3	14	9.0	TL	264	10.4	760	29.9	356	14.0	2235	88.0	8	10	1900	4180	7.1	101	130	A8/40	A8/25
11.5/80-15.3	14	9.0	TL	290	11.4	845	33.2	381	15.0	2464	97.0	9	11	2430	5346	6.5	92	139	A8/40	A8/25



PK-319 R-1

- Deep tread with excellent wear and durability
- Designed to deliver power to the ground
- Design offers maximum cleaning and hillside slip resistance

SIZE	PLY RATING	RIM WIDTH (INCH)	TYPE	SECTION WIDTH		OVERALL DIAMETER		STATIC LOADED RADIUS		ROLLING CIRCUM		NSD		LOAD CAPACITY		INFLATION PRESSURE		LOAD INDEX	SPEED	
				MM	INCH	MM	INCH	MM	INCH	MM	INCH	MM	32 ND S	KG	LBS	BAR	PSI		KMPH	MPH
18.4-26	12	16.0	TT	467	18.4	1465	57.6	635	25.0	4216	166.0	40	50	3000	6600	2.3	33	146	A6/30	A6/20