



TRENCHER I-3

- Low section Implement tires offering high load capacity with minimum soil compaction
- Ideal tires for modern farming, suitable for both on and off the-road applications

SIZE	PLY RATING	RIM WIDTH (INCH)	TYPE	SECTION WIDTH		OVERALL DIAMETER		STATIC LOADED RADIUS		ROLLING CIRCUM		NSD		LOAD CAPACITY		INFLATION PRESSURE		LOAD INDEX	SPEED	
				MM	INCH	MM	INCH	MM	INCH	MM	INCH	MM	32 ^{NDS}	KG	LBS	BAR	PSI		KMPH	MPH
31X15.50-15	10	13	TL	394	15.5	795	31.3	358	14	2362	93	22.5	28	1450	3190	3.5	50	121	A3/15	A3/9



TR-2 R-2

- Extra deep tread specially designed to get excellent traction on wet and sticky soil with excellent self-cleaning properties preventing mud clogging between the lugs
- Sidewall rubber, preventing weather cracking
- Tough tread compound to resist fast wear

SIZE	PLY RATING	RIM WIDTH (INCH)	TYPE	SECTION WIDTH		OVERALL DIAMETER		STATIC LOADED RADIUS		ROLLING CIRCUM		NSD		LOAD CAPACITY		INFLATION PRESSURE		LOAD INDEX	SPEED	
				MM	INCH	MM	INCH	MM	INCH	MM	INCH	MM	32 ^{NDS}	KG	LBS	BAR	PSI		KMPH	MPH
18.4-30	8	16	TT	465	18.3	1580	62.2	711	28	4724	186	70	88	2424	5346	1.4	20	139	A6/30	A6/20
18.4-30	10	16	TT	465	18.3	1580	62.2	711	28	4724	186	70	88	2893	6380	2.1	30	145	A6/30	A6/20
18.4-30	12	16	TT	465	18.3	1580	62.2	711	28	4724	186	70	88	3243	7150	2.3	33	149	A6/30	A6/20
18.4-30	14	16	TT	465	18.3	1580	62.2	711	28	4724	186	70	88	3442	7590	2.7	38	151	A6/30	A6/20
18.4-34	8	16	TT	465	18.3	1682	66.2	762	30	5029	198	70	88	1202	2650	1.4	20	142	A6/30	A6/20
18.4-34	10	16	TT	465	18.3	1682	66.2	762	30	5029	198	70	88	1360	3000	1.8	26	146	A6/30	A6/20
18.4-34	12	16	TT	465	18.3	1682	66.2	762	30	5029	198	70	88	1564	3450	2.2	32	151	A6/30	A6/20
18.4-34	14	16	TT	465	18.3	1682	66.2	762	30	5029	198	70	88	1610	3550	2.7	38	152	A6/30	A6/20



TR-21 R-1

- Deep tread with excellent wear and durability
- Design offers maximum cleaning and hillside slip resistance
- Designed to deliver power to the ground

SIZE	PLY RATING	RIM WIDTH (INCH)	TYPE	SECTION WIDTH		OVERALL DIAMETER		STATIC LOADED RADIUS		ROLLING CIRCUM		NSD		LOAD CAPACITY		INFLATION PRESSURE		LOAD INDEX	SPEED	
				MM	INCH	MM	INCH	MM	INCH	MM	INCH	MM	32 ^{NDS}	KG	LBS	BAR	PSI		KMPH	MPH
16.9-30	8	15.0	TT	429	16.9	1486	58.5	686	27.0	4369	172.0	36	45	2300	5070	2.1	30	137	A6/30	A6/20
18.4-30	8	16.0	TT	467	18.4	1544	60.8	711	28.0	4851	191.0	38	48	2436	5360	1.4	20	139	A6/30	A6/20
18.4-30	12	16.0	TT	467	18.4	1544	60.8	711	28.0	4851	191.0	39	50	3257	7165	2.3	33	149	A6/30	A6/20