



INDUSTRIAL

- Ribbed tread pattern
- Excellent grip on wet surfaces
- Long tread life and smooth ride

SIZE	PLY RATING	RIM WIDTH (INCH)	TYPE	SECTION WIDTH		OVERALL DIAMETER		NSD		LOAD CAPACITY		INFLATION PRESSURE		LOAD INDEX	SPEED	
				MM	INCH	MM	INCH	MM	32 ^{nds}	KG	LBS	BAR	PSI		KMPH	MPH
7.50-10	12	5.5	TT	206	8.1	645	25.3	10	13	1360	2992	7.4	105	120	A8/40	A8/25



LIFTKING HD

- Premium heavy duty forklift tire
- Suitable for material handling vehicles and mining equipment
- Thick sidewalls and tough casing provide extra durability
- Natural rubber + silica compounds provide for extended service life
- Rim guard protects beads against flats and wheel damage

SIZE	PLY RATING	RIM WIDTH (INCH)	TYPE	SECTION WIDTH		OVERALL DIAMETER		NSD		LOAD CAPACITY		INFLATION PRESSURE		LOAD INDEX	SPEED	
				MM	INCH	MM	INCH	MM	32 ^{nds}	KG	LBS	BAR	PSI		KMPH	MPH
5.70/5.00-8	10	3.0	TT	132	5.2	467	18.3	7	9	1415	3113	10.2	145	120	A6/30	A6/20
6.90/6.00-9	10	4.0	TT	160	6.3	540	21.2	10	13	1715	3773	8.7	124	126	A6/30	A6/19
6.50-10	12	5.0	TT	178	7.0	595	23.4	11	14	2180	4796	9.9	141	135	A6/30	A6/19
7.00-12	14	5.0	TT	180	7.1	690	27.1	12	15	2750	6050	9.2	131	143	A6/30	A6/19
8.25-15	16	6.5	TT	239	9.4	855	33.6	14	18	3550	7810	9.2	131	152	A6/30	A6/20
28x9-15 (8.15-15)	14	7.0	TT	213	8.4	720	33.7	16	20	3450	7590	9.0	128	154	A6/30	A6/19



ROCK PLUS HD L-4

- Premium tire, designed for heavy duty service on forklift trucks, material handling and mining equipment
- The deep tread, extra thick sidewalls and tough casing provide exceptional durability and minimize the risk of punctures and accidental damages
- Silica and natural rubber in tread compound provides greater chip and rear resistance
- Specially designed rim guard ensures protection against flats and wheel damages in the rim flange area

SIZE	PLY RATING	RIM WIDTH (INCH)	TYPE	SECTION WIDTH		OVERALL DIAMETER		NSD		LOAD CAPACITY		INFLATION PRESSURE		LOAD INDEX	SPEED	
				MM	INCH	MM	INCH	MM	32 ^{nds}	KG	LBS	BAR	PSI		KMPH	MPH
250-15	20	7.0/7.5	TT	240	9.4	845	33.2	18	23	5000	11000	10.0	142	164	A6/30	A6/20
300-15	20	8.0	TT	300	11.8	1180	46.4	22	28	6500	14300	9.0	128	173	A6/30	A6/20
10.00-20	18	7.5	TT	284	11.2	1080	42.5	30	38	6900	15180	10.2	145	175	A5/25	A5/16
12.00-20	20	8.5	TT	320	12.6	1151	45.3	34	42	9250	20350	10.2	145	185	A5/25	A5/16