



MONSTER L-5

- Extra deep skid steer tire
- Sturdy lug design
- Heat, cut and puncture resistant compounds
- Rim guard protection against flat damage

SIZE	PLY RATING	RIM WIDTH (INCH)	TYPE	SECTION WIDTH		OVERALL DIAMETER		STATIC LOADED RADIUS		ROLLING CIRCUM		NSD		LOAD CAPACITY		INFLATION PRESSURE		LOAD INDEX	SPEED	
				MM	INCH	MM	INCH	MM	INCH	MM	INCH	MM	32 ^{nds}	KG	LBS	BAR	PSI		KMPH	MPH
16.9-28	16	15.0	TL	440	17.3	1410	55.5	635	25.0	4140	163.0	36.5	46	4241	9350	3.4	50	158	A8/40	A8/25
18.4-26	16	16.0	TL	475	18.7	1425	56.1	362	25.0	4191	165.0	38.0	48	4864	10725	3.2	45	163	A8/40	A8/25
19.5L-24	16	17.0	TL	490	19.3	1298	51.1	589	23.2	3835	151.0	40.0	50	4135	9097	3.0	44	157	A8/40	A8/25



POWER LUG R-4

- Extra wide lugs designed to resist buckling, tearing and cracking
- Excellent tread wear and road ability, the laterally designed lugs result in even wear

SIZE	PLY RATING	RIM WIDTH (INCH)	TYPE	SECTION WIDTH		OVERALL DIAMETER		STATIC LOADED RADIUS		ROLLING CIRCUM		NSD		LOAD CAPACITY		INFLATION PRESSURE		LOAD INDEX	SPEED	
				MM	INCH	MM	INCH	MM	INCH	MM	INCH	MM	32 ^{nds}	KG	LBS	BAR	PSI		KMPH	MPH
16.9-24	12	15.0	TL	440	17.3	1308	51.5	584	23.0	3861	152.0	28	35	3250	7150	2.6	38	149	A8/40	A8/25
17.5L-24	12	15.0	TL	445	17.5	1270	50.0	559	22.0	3683	145.0	28	35	3150	6930	2.6	38	148	A8/40	A8/25
19.5L-24	12	17.0	TL	495	19.5	1321	52.1	584	23.0	3835	151.0	28	35	3450	7590	2.0	33	151	A8/40	A8/25
19.5L-24	16	17.0	TL	495	19.5	1325	51.9	584	23.0	3835	151.0	28	35	4135	9097	3.0	44	157	A8/40	A8/25
21L-24	12	18.0	TL	533	21.0	1377	54.2	610	24.0	3988	157.0	29	36	3875	8525	2.1	31	155	A8/40	A8/25
18.4-26	12	16.0	TL	475	18.7	1425	56.1	635	25.0	4191	165.0	28	38	4000	8800	2.4	36	156	A8/40	A8/25
16.9-28	12	15.0	TL	440	17.3	1410	55.5	635	25.0	4140	163.0	30	38	3550	7810	2.6	38	152	A8/40	A8/25