

## EV-999 EXCAVATOR



- Designed for heavy duty service
- Specially engineered tread pattern provides excellent traction, self-cleaning and on the road drive ability

SIZE	PLY RATING	RIM WIDTH (INCH)	TYPE	SECTION WIDTH		OVERALL DIAMETER		STATIC LOADED RADIUS		ROLLING CIRCUM		NSD		LOAD CAPACITY		INFLATION PRESSURE		LOAD INDEX	SPEED	
				MM	INCH	MM	INCH	MM	INCH	MM	INCH	MM	INCH	MM	32 <sup>NDS</sup>	KG	LBS		BAR	PSI
10.00-20	16	7.5 8	TT	277	10.9	1075	42.3	508	20.0	3175	125.0	24	30	3000	6600	7.6	109	146	B/50	B/30

## MONSTER G-5



- Extra deep skid steer tire
- Sturdy lug design
- Heat, cut and puncture resistant compounds
- Rim guard protection against flat damage

SIZE	PLY RATING	RIM WIDTH (INCH)	TYPE	SECTION WIDTH		OVERALL DIAMETER		STATIC LOADED RADIUS		ROLLING CIRCUM		NSD		LOAD CAPACITY		INFLATION PRESSURE		LOAD INDEX	SPEED	
				MM	INCH	MM	INCH	MM	INCH	MM	INCH	MM	32 <sup>NDS</sup>	KG	LBS	BAR	PSI		KMPH	MPH
13.00-24	16	8.0	TL	340	13.4	1280	50.4	584	23.0	3785	149.0	35.0	44	3250	7150	4.1	58	149	A8/40	A8/25
14.00-24	16	10.0	TL	375	14.7	1350	53.1	610	24.0	4013	158.0	33.5	42	3650	8030	3.8	54	149	A8/40	A8/25

## POWER GRIP G-2



- Rugged sturdy tires for drive wheels of off-the-road equipment
- Tough carcass and special tread compound with weather and ozone resistant properties to with stand cuts, snags and bruises in the most severe operating conditions
- An opened spaced traction pattern with self-cleaning property provides traction capability, ideally suited for graders

SIZE	PLY RATING	RIM WIDTH (INCH)	TYPE	SECTION WIDTH		OVERALL DIAMETER		STATIC LOADED RADIUS		ROLLING CIRCUM		NSD		LOAD CAPACITY		INFLATION PRESSURE		LOAD INDEX	SPEED	
				MM	INCH	MM	INCH	MM	INCH	MM	INCH	MM	32 <sup>NDS</sup>	KG	LBS	BAR	PSI		KMPH	MPH
13.00-24	16	8.0	TL	340	13.4	1280	50.4	584	23.0	3785	149.0	25	31	3250	7150	4.1	58	149	A8/40	A8/25
14.00-24	16	10.0	TL	375	14.7	1350	53.1	610	24.0	4013	158.0	25	31	3650	8030	3.8	54	153	A8/40	A8/25
17.5-25	16	14.0	TL	444	17.5	1331	52.4	597	23.5	3950	155.5	26	32	7300	16060	2.8	40	153	A8/40	A8/25
15.5-25	12	12	TL	386	15.2	1270	50	571	22.5	3772	148.5	24	30	2650	5830	2.5	35	142	A8/40	A8/25