

MONSTER L-5



- Extra deep skid steer tire
- Sturdy lug design
- Heat, cut and puncture resistant compounds
- Rim guard protection against flat damage

SIZE	PLY RATING	RIM WIDTH (INCH)	TYPE	SECTION WIDTH		OVERALL DIAMETER		STATIC LOADED RADIUS		ROLLING CIRCUM		NSD		LOAD CAPACITY		INFLATION PRESSURE		LOAD INDEX	SPEED	
				MM	INCH	MM	INCH	MM	INCH	MM	INCH	MM	32 ^{nds}	KG	LBS	BAR	PSI		KMPH	MPH
10-16.5	12	8.25	TL	259	10.2	798	31.4	366	14.4	2337	92.0	43	53.7	2180	4796	4.4	64	135	A5/25	A5/16
12-16.5	14	9.75	TL	307	12.1	838	33.0	384	15.1	2515	99.0	44	55.0	2765	6083	4.8	70	144	A5/25	A5/16
14-17.5	14	10.5	TL	358	14.1	935	36.8	427	16.8	2743	108.0	44	55.0	3900	8580	5.5	78	155	A5/25	A5/16

ROCK MASTER R-4



- Deeper tread for longer life, bigger and sturdier block
- Excellent chip and tear resistance compound
- Extra thick sidewall with rim guard, gives protection against damages

SIZE	PLY RATING	RIM WIDTH (INCH)	TYPE	SECTION WIDTH		OVERALL DIAMETER		STATIC LOADED RADIUS		ROLLING CIRCUM		NSD		LOAD CAPACITY		INFLATION PRESSURE		LOAD INDEX	SPEED	
				MM	INCH	MM	INCH	MM	INCH	MM	INCH	MM	32 ^{nds}	KG	LBS	BAR	PSI		KMPH	MPH
10-16.5	12	8.25	TL	266.7	10.5	789.9	31.1	355.6	14.0	2336.8	92.0	28.5	36	2175	4796	5.17	75	135	A5/25	A5/16
12-16.5	14	9.75	TL	325.1	12.8	855.9	33.7	381	15.0	2514.6	99.0	30.0	38	2759	6083	4.83	70	144	A5/25	A5/16

ROCK PLUS HD L-4



- Premium tire, designed for heavy duty service on forklift trucks, material handling and mining equipment
- The deep tread, extra thick sidewalls and touch casing provide exceptional durability and minimize the risk of punctures and accidental damages
- Silica and natural rubber in tread compound provides greater chip and rear resistance
- Specially designed rim guard ensures protection against flats and wheel damages in the rim flange area

SIZE	PLY RATING	RIM WIDTH (INCH)	TYPE	SECTION WIDTH		OVERALL DIAMETER		STATIC LOADED RADIUS		ROLLING CIRCUM		NSD		LOAD CAPACITY		INFLATION PRESSURE		LOAD INDEX	SPEED	
				MM	INCH	MM	INCH	MM	INCH	MM	INCH	MM	32 ^{nds}	KG	LBS	BAR	PSI		KMPH	MPH
10-16.5	12	8.25	TL	268	10.5	790	31.1	356	14.0	2286	90.0	30	38	2140	4708	5.2	74	134	A5/25	A5/16
12-16.5	14	9.75	TL	325	12.8	866	34.1	381	15.0	2438	96.0	30	38	2240	4928	6.2	89	136	A5/25	A5/16