



STEERKING HD+ R-4

- Premium conventional skid steer tire
- Heavy sidewall protects against snags and punctures
- Deep thread and solid lugs for superior grip and control

SIZE	PLY RATING	RIM WIDTH (INCH)	TYPE	SECTION WIDTH		OVERALL DIAMETER		STATIC LOADED RADIUS		ROLLING CIRCUM		NSD		LOAD CAPACITY		INFLATION PRESSURE		LOAD INDEX	SPEED	
				MM	INCH	MM	INCH	MM	INCH	MM	INCH	MM	32 ^{nds}	KG	LBS	BAR	PSI		KMPH	MPH
10-16.5	12	8.25	TL	268	10.5	795	31.3	356	14.0	2286	90.0	16	20	1700	3740	5.3	75	126	A5/40	A5/25
12-16.5	12	9.75	TL	325	12.8	853	33.6	381	15.0	2438	96.0	20	25	2060	4532	5.2	74	132	A5/25	A5/16



STEER PLUS HD R-4

- Premium conventional skid steer tire
- Reinforced sidewall gives added protection against snags and punctures
- Deep tread and solid lugs for superior grip and control
- Specially designed rim guard protects the rim against flat damage

SIZE	PLY RATING	RIM WIDTH (INCH)	TYPE	SECTION WIDTH		OVERALL DIAMETER		STATIC LOADED RADIUS		ROLLING CIRCUM		NSD		LOAD CAPACITY		INFLATION PRESSURE		LOAD INDEX	SPEED	
				MM	INCH	MM	INCH	MM	INCH	MM	INCH	MM	32 ^{nds}	KG	LBS	BAR	PSI		KMPH	MPH
23X8.50-12	6	7.0	TL	216	8.5	584	23.0	254	10.0	1727	68.0	12	15	615	1353	3.4	50	90	A5/25	A5/16
27X8.50-15	8	7.0	TL	218	8.6	676	26.6	218	8.6	2006	79.0	12	15	915	2090	4.2	61	106	A5/25	A5/16
33X15.5-16.5	14	12.0	TL	394	15.5	838	33.0	381	15.0	2464	97.0	19	24	3150	6930	5.2	74	148	A5/25	A5/16
14-17.5	14	10.5	TL	348	13.7	940	37.0	406	16.0	2743	108.0	26	33	2900	6380	5.5	79	145	A5/25	A5/16
15-19.5	14	11.8	TL	401	15.8	1036	40.8	457	18.0	3048	120.0	26	33	3350	7370	4.8	70	150	A5/25	A5/16

