

# LIGHT TRUCK



## LOAD KING

- Strong and wider lug with strong casing for uniform wear and long life

| SIZE    | PLY RATING | RIM WIDTH (INCH) | TYPE | SECTION WIDTH |      | OVERALL DIAMETER |      | NSD |                   | LOAD CAPACITY |      | INFLATION PRESSURE |     | LOAD INDEX | SPEED |      |
|---------|------------|------------------|------|---------------|------|------------------|------|-----|-------------------|---------------|------|--------------------|-----|------------|-------|------|
|         |            |                  |      | MM            | INCH | MM               | INCH | MM  | 32 <sup>nds</sup> | KG            | LBS  | BAR                | PSI |            | KMPH  | MPH  |
| 7.50-16 | 16         | 6.0              | TT   | 218           | 8.6  | 823              | 32.4 | 16  | 20                | 1600          | 3520 | 7.7                | 109 | 124        | J/100 | J/60 |
| 8.25-16 | 16         | 6.5              | TT   | 231           | 9.1  | 841              | 33.6 | 18  | 23                | 1850          | 4070 | 7.7                | 109 | 129        | J/100 | J/60 |



## MILEAGE MAKER

- It delivers high mileage in its category
- Designed for heavy duty applications

| SIZE    | PLY RATING | RIM WIDTH (INCH) | TYPE | SECTION WIDTH |      | OVERALL DIAMETER |      | NSD |                   | LOAD CAPACITY |      | INFLATION PRESSURE |     | LOAD INDEX | SPEED |      |
|---------|------------|------------------|------|---------------|------|------------------|------|-----|-------------------|---------------|------|--------------------|-----|------------|-------|------|
|         |            |                  |      | MM            | INCH | MM               | INCH | MM  | 32 <sup>nds</sup> | KG            | LBS  | BAR                | PSI |            | KMPH  | MPH  |
| 7.00-15 | 12         | 5.5              | TT   | 206           | 8.1  | 770              | 30.3 | 15  | 19                | 1180          | 2596 | 6.3                | 89  | 162        | J/100 | J/60 |



## MILESTONE

- Highway tire for trailer and light truck applications
- Durable with excellent grip

| SIZE        | PLY RATING | RIM WIDTH (INCH) | TYPE | SECTION WIDTH |      | OVERALL DIAMETER |      | NSD |                   | LOAD CAPACITY |      | INFLATION PRESSURE |     | LOAD INDEX | SPEED |      |
|-------------|------------|------------------|------|---------------|------|------------------|------|-----|-------------------|---------------|------|--------------------|-----|------------|-------|------|
|             |            |                  |      | MM            | INCH | MM               | INCH | MM  | 32 <sup>nds</sup> | KG            | LBS  | BAR                | PSI |            | KMPH  | MPH  |
| 7.00-16     | 14         | 14.0             | TT   | 206           | 8.1  | 785              | 30.9 | 12  | 15                | 1320          | 2904 | 7.0                | 89  | 118        | J/100 | J/60 |
| 7.00-16     | 14         | 5.5              | TT   | 206           | 8.1  | 785              | 30.9 | 13  | 17                | 1150          | 2530 | 6.3                | 89  | 113        | J/100 | J/60 |
| 7.00-16(DB) | 16         | 6.5              | TT   | 239           | 9.4  | 855              | 33.6 | 14  | 18                | 3550          | 7810 | 9.2                | 131 | 152        | J/100 | J/60 |
| 7.50-16     | 14         | 6.0              | TT   | 218           | 8.6  | 823              | 32.4 | 12  | 15                | 1500          | 3300 | 7.0                | 99  | 122        | J/100 | J/60 |
| 7.50-16     | 10         | 6.0              | TL   | 218           | 8.6  | 823              | 32.4 | 8   | 10                | 1590          | 3498 | 5.6                | 7.8 | 124        | P/150 | P/94 |
| 8.25-16     | 14         | 6.5              | TT   | 231           | 9.1  | 841              | 33.1 | 12  | 15                | 1700          | 3740 | 6.4                | 91  | 126        | J/100 | J/60 |



## SILVERSTONE

- Regular mileage rib tire
- Suitable for heavy duty and mixed operation

| SIZE    | PLY RATING | RIM WIDTH (INCH) | TYPE | SECTION WIDTH |      | OVERALL DIAMETER |      | NSD |                   | LOAD CAPACITY |      | INFLATION PRESSURE |     | LOAD INDEX | SPEED |      |
|---------|------------|------------------|------|---------------|------|------------------|------|-----|-------------------|---------------|------|--------------------|-----|------------|-------|------|
|         |            |                  |      | MM            | INCH | MM               | INCH | MM  | 32 <sup>nds</sup> | KG            | LBS  | BAR                | PSI |            | KMPH  | MPH  |
| 6.50-16 | 12         | 4.5              | TT   | 185           | 7.3  | 765              | 30.1 | 10  | 13                | 1080          | 2375 | 7.1                | 101 | 111        | J/100 | J/60 |