

AGRICULTURAL RADIAL - R1W SERIES

SR-777 (R1W)



- Radial tire with balanced characteristics for a wide range of applications both in the field on the road
- Larger ground contact patch makes the tire well suited for handling grassland
- Long service life thanks to the use of a wear resistant tread compound
- Deeper tread providing longer tire life
- Prominent rim guard, protecting rim flange from damage

SIZE	RIM WIDTH (INCH)	TYPE	SECTION WIDTH		OVERALL DIAMETER		STATIC LOADED RADIUS		ROLLING CIRCUM		NSD		LOAD CAPACITY		INFLATION PRESSURE		LOAD INDEX	SPEED	
			MM	INCH	MM	INCH	MM	INCH	MM	INCH	MM	32 ND S	KG	LBS	BAR	PSI		KMPH	MPH
280/70R-16	W9/W10	TL	282	11.1	798	31.4	356	14.0	2370	93.3	32	40	1050	2310	2.0	29	110	B/50	B/30
280/70R-18	W9/W10	TL	282	11.1	849	33.4	381	15.0	2547	100.3	32	40	1120	2465	2.0	29	112	B/50	B/30
420/70R-28	W13/W14	TL	419	16.5	1349	53.1	610	24.0	3988	157.0	46	58	2064	4540	1.6	23	133	B/50	B/30

SR-888 (R1W)



- Radial tire with balanced characteristics for a wide range of applications both in the field on the road
- Larger ground contact patch makes the tire well suited for handling grassland
- Long service life thanks to the use of a wear resistant tread compound
- Deeper tread providing longer tire life
- Prominent rim guard, protecting rim flange from damage

SIZE	RIM WIDTH (INCH)	TYPE	SECTION WIDTH		OVERALL DIAMETER		STATIC LOADED RADIUS		ROLLING CIRCUM		NSD		LOAD CAPACITY		INFLATION PRESSURE		LOAD INDEX	SPEED	
			MM	INCH	MM	INCH	MM	INCH	MM	INCH	MM	32 ND S	KG	LBS	BAR	PSI		KMPH	MPH
280/85R-24	W10/W9	TL	282	11.1	1087	42.8	508	20.0	3429	135.0	36	45	1215	2673	1.6	23	115	B/50	B/30
340/85R-24	W12/W11	TL	343	13.5	1188	46.8	533	21.0	3531	139.0	42	52	1650	.63.	1.6	23	125	B/50	B/30
380/85R-24	W12/W13	TL	381	15.0	1255	49.4	559	22.0	3706	145.9	40	55	1955	4301	1.6	23	131	B/50	B/30
320/85R-28	W11/W10	TL	320	12.6	1255	49.4	559	22.0	3734	147.0	42	53	1600	3520	1.6	23	124	B/50	B/30
340/85R-28	W12/W11	TL	353	13.6	1288	50.7	584	23.0	3835	151.0	44	55	1755	3861	1.6	23	137	B/50	B/30
380/85R-28	W12/W13	TL	381	15.0	1356	53.4	610	24.0	4013	158.0	45	56	2360	4532	1.6	23	133	B/50	B/30
420/85R-28	W15/W14	TL	419	16.5	1425	56.1	635	25.0	4242	167.0	50	62	2430	5346	1.6	23	139	B/50	B/30
380/85R-30	W12/W13	TL	381	15.0	1407	55.4	630	24.8	4153	163.5	46	58	2180	4796	1.6	23	135	B/50	B/30
420/85R-30	W15/W14	TL	419	16.5	1476	58.1	660	26.0	4394	173	46	58	2500	5500	1.6	23	140	B/50	B/30
380/85R-34	W12/W13	TL	381	15.0	1808	71.2	686	27.0	4470	176.0	43	54	2300	5060	1.6	23	137	B/50	B/30
420/85R-34	W15/W14	TL	419	16.5	1577	62.1	711	28.0	4674	184.0	46	58	2650	5830	1.6	23	142	B/50	B/30
460/85R-34	W16/W15	TL	475	18.7	1646	64.8	737	29.0	4851	191.0	46	58	3082	6780	1.6	23	142	B/50	B/30
420/85R-38	W15/W14	TL	419	16.5	1679	66.1	762	30.0	5004	197.0	51	64	2800	6160	1.6	23	144	B/50	B/30
460/85R-38	W16/W15	TL	455	17.9	1748	68.8	787	31.0	5156	203.0	54	68	3250	7150	1.6	23	149	B/50	B/30
520/85R-38	W16/DW18	TL	516	20.3	1849	72.8	813	32.0	5410	213.0	50	63	3875	8525	1.6	23	155	B/50	B/30
480/80R-42	W16/DW16	TL	480	18.9	1836	72.3	762	30.0	5461	215.0	54	68	3450	7590	1.6	23	151	B/50	B/30
520/85R-42	W16/DW16	TL	516	20.3	1951	76.8	859	33.8	5735	225.8	50	63	4136	9100	1.6	23	151	B/50	B/30
480/80R-46	W16/DW16	TL	480	18.9	1933	76.1	889	35.0	5791	228.0	54	68	4259	9370	2.4	34	158	B/50	B/30
340/85R-48	W12/W11	TL	353	13.9	1798	70.8	838	33.0	5385	212.0	37	46	3557	7825	4.1	58	152	B/50	B/30