

# AGRICULTURAL RADIAL - R1W SERIES



## RC-999 (R1W)

- Round shoulders minimize influence on the crop roots
- Optimum lug shape and angle provide excellent grip
- Long service life thanks to the use of a wear resistant tread compound
- Special line for crop applications

SIZE	RIM WIDTH (INCH)	TYPE	SECTION WIDTH		OVERALL DIAMETER		STATIC LOADED RADIUS		ROLLING CIRCUM		NSD		LOAD CAPACITY		INFLATION PRESSURE		LOAD INDEX	SPEED	
			MM	INCH	MM	INCH	MM	INCH	MM	INCH	MM	32 <sup>NDS</sup>	KG	LBS	BAR	PSI		KMPH	MPH
210/95R-32	W8/W7	TL	214	8.4	1213	47.8	559	22.0	3658	144.0	28	35	1400	3080	2.5	36	120	B/50	B/30
230/95R-32	W8/W7	TL	228	9.0	1251	49.3	584	23.0	3759	148.0	30	38	1800	3960	4.1	58	128	B/50	B/30
270/95R-32	W8/W10	TL	275	10.8	1327	52.2	609	24.0	5004	197.0	31	39	2240	4928	4.1	58	136	B/50	B/30
230/95R-36	W8/W7	TL	228	9.0	1352	53.2	609	24.0	4064	160.0	42	53	1900	4180	4.1	58	130	B/50	B/30
270/95R-38	W8/W10	TL	264	10.3	1479	58.2	686	27.0	4445	175.0	35	44	2505	5511	4.1	58	140	B/50	B/30
230/95R-44	W8/W7	TL	228	9.0	1556	61.3	737	29.0	4699	185.0	32	40	2120	4664	4.1	58	134	B/50	B/30
270/95R-44	W8/W10	TL	275	10.8	1632	64.3	762	30.0	4902	193.0	32	40	2650	5830	4.1	58	142	B/50	B/30
300/95R-46	W8/W11	TL	305	12.0	1737	68.3	813	32.0	5207	205.0	45	57	3157	6945	4.1	58	148	B/50	B/30
230/95R-48	W8/W7	TL	228	9.0	1657	65.2	787	30.1	4978	196.0	32	40	2240	4928	4.1	58	136	B/50	B/30
270/95R-48	W8/W10	TL	275	10.8	1733	68.2	812	32.0	5257	207.0	31	39	2800	6160	4.1	58	144	B/50	B/30
300/95R-52	W10/W11	TL	305	12.0	1892	75.0	889	35.0	5664	223.0	52	65	3457	7605	4.1	58	151	B/50	B/30

# AGRICULTURAL BIAS



## FARM SERVICE I-1

- Low section implement tires offering high load capacity with minimum soil compaction
- Ideal tires for modern farming, suitable for both on and off-the-road applications

SIZE	PLY RATING	RIM WIDTH (INCH)	TYPE	SECTION WIDTH		OVERALL DIAMETER		STATIC LOADED RADIUS		ROLLING CIRCUM		NSD		LOAD CAPACITY		INFLATION PRESSURE		LOAD INDEX	SPEED	
				MM	INCH	MM	INCH	MM	INCH	MM	INCH	MM	32 <sup>NDS</sup>	KG	LBS	BAR	PSI		KMPH	MPH
11L-15	8	8.0	TL	270	10.6	790	31.1	330	13	2261	89	8	10	1150	2530	2.5	36	113	D/65	D/40
11L-15	12	8.0	TL	270	10.6	790	31.1	330	13	2261	89	8	10	1450	3190	3.6	51	121	D/65	D/40
12.5L-15	12	10.0	TL	310	12.2	818	32.2	356	14	2413	95	9	11	1750	3850	3.7	52	128	D/65	D/40