RADIAL HARVESTER

SR-65

R-1

- Suitable for all kinds of Harvesting Machines
- Design to deliver power to the ground
- Extra deep tread
- Low soil compaction and excellent traction in the field

SIZE	PATTERN	RIM WIDTH		TYPE	SECTION WIDTH		OVERALL DIAMETER		STATIC LOADED RADIUS		ROLLING CIRCUM ± 2.5 %		NSD		LOAD CAPACITY 40 kmph / 25 mph MAX LOAD		LOAD CAPACITY 50 kmph / 30 mph MAX LOAD		INFLATION PRESSURE		LOAD INDEX	SPEED	
		REC	ALT		mm	inch	mm	inch	mm	inch	mm	inch	mm	32nds	kg	lbs	kg	lbs	bar	psi		kmph	mph
750/65R-26 28L R-26 166 A8/B	SR-65	DW 25B	DW 23B	TL	765	30.1	1636	64.4	714	28.1	4907	193.2	50	62	6900	15180	6150	13530	3.0	42	171	B/50kmph	B/30 mph
800/65R-32 30.5LR-32 181 A8/178 B		DW 27B	DW 25B DW 27B		818	32.2	1855	73.2	838	33.0	5588	220.0	46	58	8250	18150	7500	16500	3.6	52	178	B/40kmph	B/25 mph

Tolerances: O.D. ±2.5% - S.W. ±2.5% - RC ±2.5%