SR-888

RADIAL R-1W

80/85 SERIES

- Radial tire with balanced characteristics for wide range of applications both on the field and on the road
- Larger ground contact patch makes the tire well suited for handling grassland
- Long service life thanks to the use of a wear resistant tread compound
- Deeper Tread providing longer tire life
- Prominent Rim Guard, protecting rim flange from damage

SIZE	PATTERN	RIM WIDTH		TYPE	SECTION WIDTH		OVERALL DIAMETER		STATIC LOADED RADIUS		ROLLING CIRCUM ± 2.5 %		NSD		LOAD CAPACITY 40 kmph / 25 mph MAX LOAD		LOAD CAPACITY 50 kmph / 30 mph MAX LOAD		INFLATION PRESSURE		LOAD INDEX	SPEED	
		REC	ALT		mm	inch	mm	inch	mm	inch	mm	inch	mm	32nds	kg	lbs	kg	lbs	bar	psi		kmph	mph
250/85R-20 9.5R-20 116 A8/B	SR-888	W 8	W 7 W 9	TL	249	9.8	940	37.0	424	16.7	2812	110.7	38	48	1250	2750	1250	2750	2.4	35	116	B/50 kmph	B/30 mph
280/85R-20 11.2R-20 112 A8/B		W 10	W 9		292	11.5	983	38.7	442	17.4	2951	116.2	39	49	1120	2464	1120	2464	1.6	23	112		
250/85R-24 9.5R-24 109 A8/B		W 8	W 7 W 9		251	9.9	1036	40.8	475	18.7	3104	122.2	42	53	1030	2465	1030	2465	1.6	23	109		
280/85R-24 11.2R-24 115 A8/B		W 10	W 9		292	11.5	1087	42.8	508	20.0	3226	127.0	41	51	1215	2675	1215	2675	1.6	23	115		
320/85R-24 12.4R-24 122 A8/B		W 11	W 9 W 10		330	13.0	1153	45.4	518	20.4	3424	134.8	43	54	1500	3300	1500	3300	1.6	23	122		
340/85R-24 13.6R-24 125 A8/B		W 12	W 11		343	13.5	1188	46.8	533	21.0	3531	139.0	44	55	1650	3630	1650	3630	1.6	23	125		
380/85R-24 14.9R-24 131 A8/B		W 12	W 11 W 13		381	15.0	1255	49.4	559	22.0	3706	145.9	45	56	1950	4290	1950	4290	1.6	23	131		
250/85R-28 9.5R-28 112 A8/B	SR-888	W 8	W 7 W 9	TL	251	9.9	1138	44.8	518	20.4	3321	134.7	38	48	1120	2465	1120	2465	1.6	23	112	B/50 kmph	B/30 mph
280/85R-28 11.2R-28 118 A8/B		W 10	W 9		292	11.5	1186	46.7	546	21.5	3559	140.1	42	53	1320	2904	1320	2904	1.6	23	118		
320/85R-28 12.4R-28 124 A8/B		W 11	W 9 W 10		320	12.6	1255	49.4	559	22.0	3734	147.0	42	53	1600	3520	1600	3520	1.6	23	124		
340/85R-28 13.6R-28 127 A8/B		W 12	W 11		353	13.9	1288	50.7	584	23.0	3835	151.0	42	53	1750	3850	1750	3850	1.6	23	127		
380/85R-28 14.9R-28 133 A8/B		W 12	W 11 W 13		381	15.0	1356	53.4	607	23.9	4016	158.1	45	56	2060	4535	2060	4535	1.6	23	133		
420/85R-28 16.9R-28 139 A8/B		W 15	W 13 W 14		419	16.5	1425	56.1	635	25.0	4242	167.0	49	61	2430	5345	2430	5345	1.6	23	139		
380/85R-30 14.9R-30 135 A8/B	SR-888	W 12	W 11 W 13	TL	381	15.0	1407	55.4	630	24.8	4153	163.5	45	56	2180	4796	2180	4796	1.6	23	135	B/50 kmph	B/30 mph
420/85R-30 16.9R-30 140 A8/B		W 15	W 13 W 14		419	16.5	1476	58.1	660	26.0	4394	173.0	45	56	2500	5500	2500	5500	1.6	23	140		
460/85R-30 18.4R-30 145 A8/B		W 16 L	W 14 L W 15 L		475	18.7	1544	60.8	683	26.9	4536	178.6	54	67	2900	6380	2900	6380	1.6	23	145		

Tolerances: O.D. ± 2.5% - S.W. ± 2.5% - RC ± 2.5%

AGRICULTURE

SIZE	PATTERN	RIM WIDTH		TYPE	SECTION WIDTH		OVERALL DIAMETER		STATIC LOADED RADIUS		ROLLING CIRCUM ± 2.5 %		NSD		LOAD CAPACITY 40 kmph / 25 mph MAX LOAD		LOAD CAPACITY 50 kmph / 30 mph MAX LOAD		INFLATION PRESSURE		LOAD INDEX	SPEED	
		REC	ALT		mm	inch	mm	inch	mm	inch	mm	inch	mm	32nds	kg	lbs	kg	lbs	bar	psi		kmph	mph
380/85R-34 14.9R-34 137 A8 /B	SR-888	W 12	W 11 W 13	TL	381	15.0	1514	59.6	686	27.0	4470	176.0	45	56	2300	5060	2300	5060	1.6	23	137	B/50 Kmph	B/30 mph
420/85R-34 16.9R-34 142 A8/B		W 15	W 13 W 14		419	16.5	1577	62.1	711	28.0	4674	184.0	49	61	2650	5830	2650	5830	1.6	23	142		
460/85R-34 18.4R-34 147 A8/B		W 16	W 14 W 15		475	18.7	1646	64.8	737	29.0	4851	191.0	50	63	3075	6765	3075	6765	1.6	23	147		
340/85R-38 13.6R-38 133 A8/B	SR-888	W 12	W 11	TL	353	13.9	1543	60.7	712	28.0	4668	183.8	52	65	2060	4532	2060	4532	1.6	23	133	B/50 Kmph	B/30 mph
420/85R-38 16.9R-38 144 A8/B		W 15	W 13 W 14		419	16.5	1679	66.1	762	30.0	5004	197.0	52	65	2800	6160	2800	6160	1.6	23	144		
460/85R-38 18.4R-38 149 A8/B		W 16	W 14 W 15		455	17.9	1748	68.8	787	31.0	5156	203.0	55	69	3250	7150	3250	7150	1.6	23	149		
520/85R-38 20.8R-38 155 A8/B		DW 18	DW 16L DW 18L		516	20.3	1849	72.8	813	32.0	5410	213.0	59	74	3875	8525	3875	8525	1.6	23	155		
480/80R-42 18.4R-42 151 A8/B	SR-888	W 16	DW 16	TL	480	18.9	1836	72.3	838	33.0	5461	215.0	54	68	3450	7590	3450	7590	1.6	23	151	B/50 Kmph	B/30 mph
520/85R-42 20.8R-42 157 A8/B		DW 18L	DW 16		516	20.3	1951	76.8	859	33.8	5735	225.8	58	73	4125	9075	4125	9075	1.6	23	157		
480/80R-46 18.4R-46 158 A8/B	SR-888	W 16	DW 16	TL	480	18.9	1933	76.1	889	35.0	5791	228.0	52	65	4250	9350	4250	9350	2.4	35	158	B/50 Kmph	B/30 mph
340/85R-48 13.6R-48 152 A8/B		W 12	W 11		353	13.9	1798	70.8	838	33.0	5385	212.0	44	55	3550	7810	3550	7810	4.1	58	152		

Tolerances: O.D. ± 2.5% - S.W. ± 2.5% - RC ± 2.5%