MONSTER

L-5

- Extra deep tread with sturdy lug design
- Strong casing with heat and cut resistant tread compound provide longer life
- Extra thick side wall with rim guard gives protection against damage

SIZE	PATTERN	PLY RATING	RIM WIDTH	TYPE	SECTION WIDTH		OVERALL DIAMETER		STATIC LOADED RADIUS		ROLLING CIRCUM ± 2.5 %		NSD		LOAD CAPACITY		INFLATION PRESSURE		LOAD INDEX	SPEED	
																				kmph	mph
			inch		mm	inch	mm	inch	mm	inch	mm	inch	mm	32nds	kg	lbs	bar	psi			
11L-16	MONSTER L-5	14	8.0	TL	280	11.0	820	32.3	381	15.0	2438	96.0	22	27	1360	2992	4.8	70	119	A8/40 kmph	A8/25 mph
12.5/80-18		12	9.0		305	12.0	975	38.4	432	17.0	2896	114.0	34	43	2120	4665	3.1	45	134		
		16													2650	5830	3.6	55	142		
19.5L-24		16	17.0		490	19.3	1298	51.1	589	23.2	3835	151.0	41	51	4125	9075	3.0	44	157		
18.4-26		16	16.0		475	18.7	1425	56.1	635	25.0	4191	165.0	39	49	4875	10725	3.1	45	163		
16.9-28		16	15.0		440	17.3	1410	55.5	635	25.0	4140	163.0	36	45	4250	9350	3.1	45	158		

Tolerances: O.D. ± 2.5% - S.W. ± 2.5% - RC ± 2.5%