ROAD KING

C-1

- Speedways compactor tire are engineered to provide even distribution of ground pressure & to give optimum compaction
- Tread compound specially formulated to endure high temperatures and minimize loose materials sticky to tire

SIZE	PATTERN	PLY RATING	RIM WIDTH	TYPE	SECTION WIDTH		OVERALL DIAMETER		LOAD CAPACITY				INFLATION PRESSURE		LOAD INDEX	SPEED	
									10 KPH MAX LOAD		20 KPH MAX LOAD					kmph	mph
			inch		mm	inch	mm	inch	kg	lbs	kg	lbs	bar	psi			
7.50-15	ROADKING	6	6.0	TT/TL	226	8.9	790	31.1	1700	3740	1500	3300	3.9	57	122	A4/20 kmph	A4/12 mph
		14							2800	6160	2300	5060	8.6	125	137		
8.5/90-15K		14	6.0		231	9.1	785	30.9	3000	6600	2240	4928	3.4	50	136		
9.00-20		12	7.0		274	10.8	1016	40.0	4125	9075	3150	6930	6.2	90	148		
		14							4500	9900	3450	7590	7.2	104	151		
11.00-20		16	8.0		305	12.0	1082	42.6	5450	11990	4375	9625	7.2	104	159		
		18							6000	13200	4625	10175	8.1	118	161		

Tolerances: O.D. ± 2.5% - S.W. ± 2.5% - RC ± 2.5%