# SAND GRIP

## 4X4 TYRES

- Built to withstand rough terrain, heavy loads and harsh conditions
- Typically constructed with high strength materials to resist punctures, tears and damage

| SIZE | PATTERN | PLY RATING | RIM WIDTH | TYPE | SECTION WIDTH | | OVERALL DIAMETER | | STATIC LOADED RADIUS | | ROLLING CIRCUM ± 2.5 % | | NSD | | LOAD CAPACITY | | INFLATION PRESSURE | | LOAD INDEX | SPEED | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | | | | | | | | | | | | | | | kmph | mph |
| | | | inch | | mm | inch | mm | inch | mm | inch | mm | inch | mm | 32nds | kg | lbs | bar | psi | | | |
| 7.50-16 | SANDGRIP | 12 | 6.0 | TT | 221 | 8.7 | 825 | 32.5 | 374 | 14.7 | 2393 | 94.2 | 13 | 16 | 1250 | 2750 | 6.2 | 90 | 116 | G/90 kmph | G/56 mph |
| 12.00-20 | | 18 | 8.5 | | 320 | 12.6 | 1138 | 44.8 | 524 | 20.6 | 3360 | 132.3 | 21 | 26 | 3250 | 7150 | 7.3 | 105 | 149 | | |

Tolerances: O.D. ± 2.5% - S.W. ± 2.5% - RC ± 2.5%