SKID STEER

MONSTER

- Extra deep tread with sturdy lug design
- Strong casing with heat and cut resistant tread compound provide longer life
- Extra thick side wall with rim guard gives protection against damage

SIZE	PATTERN	PLY RATING	RIM WIDTH	TYPE	SECTION WIDTH		OVERALL DIAMETER		STATIC LOADED RADIUS		ROLLING CIRCUM ± 2.5 %		NSD		LOAD CAPACITY		INFLATION PRESSURE		LOAD INDEX	SPEED	
																				kmph	mph
			inch		mm	inch	mm	inch	mm	inch	mm	inch	mm	32nds	kg	lbs	bar	psi			
23x8.50-12	MONSTER L-5	8	7.0	TL	216	8.5	584	23.0	254	10.0	1727	68.0	19	24	690	1518	3.5	50	90	A5/25 kmph	A5/16 mph
27x8.50-12		10			218	8.6	676	26.6	305	12.0	2006	79.0	23	29	1000	2200	4.3	61	106		
10.0/75-15.3		14	9.0	TL	259	10.2	775	30.5	356	14.0	2311	91.0	34	43	2120	4664	4.7	68	134	A6/30 kmph	A6/18 mph
10-16.5		12	8.25	TL	259	10.2	798	31.4	366	14.4	2337	92.0	37	46	2180	4796	4.4	64	135	A8/40 kmph	A8/20 mph
12-16.5		14	9.75		307	12.1	838	33.0	384	15.1	2515	99.0	37	46	2765	6083	4.8	70	144		
14-17.5		14	10.5	TL	358	14.1	935	36.8	427	16.8	2743	108.0	36	45	3900	8580	5.5	78	155	A5/25 kmph	A5/16 mph

Tolerances: O.D. ± 2.5% - S.W. ± 2.5% - RC ± 2.5%